

Designation				Principal dimensions (mm)					Basic load ratings(N)		Basic load ratings(kgf)		Speed ratings(rpm)			Abutment and fillet dimensions (mm)						Weight(g)	
轴承代号				外形尺寸					额定载荷(N)		额定载荷(kgf)		极限转速(rpm)			安装尺寸(mm)						重量(g)	
Open type	With shield	With seal VV	With seal DD	d	D	B	B1	r ⁽¹⁾	Cr	Cor	Cr	Cor	Grease 脂润滑		Oil 油润滑	d _a	d _b	Da	Db	r _a	r _b	Open type	With shield
开放型	防尘盖型	密封式VV	密封式DD					Min (最小)					ZZ	D-D	Z	Min (最小)	Max(最大)	Max(最大)	Min (最小)	Max(最大)	Max(最大)	开放型	防尘盖型
623	623ZZ	-	-	3	10	4	4	0.15	630	218	64	22	50000	-	60000	4.2	4.3	8.8	8	0.15	0.15	1.65	1.66
624	624ZZ	-	-	4	13	5	5	0.2	1300	485	133	49	40000	-	48000	5.6	6	11.4	11.3	0.2	0.2	3.03	3.04
625	625ZZ1	625VV	625DD	5	16	5	5	0.3	1730	670	177	68	36000	32000	43000	7	7.5	14	13.8	0.3	0.3	4.95	4.86
626	626ZZ1	626VV	626DD	6	19	6	6	0.3	2340	885	238	90	32000	30000	40000	8	8.5	17	16.5	0.3	0.3	8.15	7.94
627	627ZZ	627VV	627DD	7	22	7	7	0.3	3300	1370	335	140	30000	28000	36000	9	10.5	20	19	0.3	0.3	12.7	12.9
628	628ZZ	628VV	628DD	8	24	8	8	0.3	3350	1430	340	146	28000	24000	34000	10	12	22	20.5	0.3	0.3	17.2	17.4
629	629ZZ	629VV	629DD	9	26	8	8	-0.6	4550	1970	465	201	28000	22000	34000	11	12.8	24	22.8	0.3	0.3	19.5	19.3