



Unit Number	Bearing Number	Shaft Size	D Dimension	B Dimension	C Dimension	Basic Load	
						Ratings	
						Cr	Cor
SSUC201	SSUC201	12 mm	47.0 mm 1.850 in	31.0 mm 1.220 in	16.0 mm 0.630 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSUC201-8	SSUC201-8	1/2 in	47.0 mm 1.850 in	31.0 mm 1.220 in	16.0 mm 0.630 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSUC202	SSUC202	15 mm	47.0 mm 1.850 in	31.0 mm 1.220 in	16.0 mm 0.630 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSUC202-10	SSUC202-10	5/8 in	47.0 mm 1.850 in	31.0 mm 1.220 in	16.0 mm 0.630 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSUC203	SSUC203	17 mm	47.0 mm 1.850 in	31.0 mm 1.220 in	16.0 mm 0.630 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSUC204-12	SSUC204-12	3/4 in	47.0 mm 1.850 in	31.0 mm 1.220 in	16.0 mm 0.630 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSUC204	SSUC204	20 mm	47.0 mm 1.850 in	31.0 mm 1.220 in	16.0 mm 0.630 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSUC205-14	SSUC205-14	7/8 in	52.0 mm 2.047 in	34.1 mm 1.343 in	17.0 mm 0.669 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSUC205-15	SSUC205-15	15/16 in	52.0 mm 2.047 in	34.1 mm 1.343 in	17.0 mm 0.669 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSUC205	SSUC205	25 mm	52.0 mm 2.047 in	34.1 mm 1.343 in	17.0 mm 0.669 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSUC205-16	SSUC205-16	1 in	52.0 mm 2.047 in	34.1 mm 1.343 in	17.0 mm 0.669 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSUC206-18	SSUC206-18	1-1/8 in	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSUC206	SSUC206	30 mm	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSUC206-19	SSUC206-19	1-3/16 in	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSUC206-20	SSUC206-20	1-1/4 in	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSUC207-20	SSUC207-20	1-1/4 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb
SSUC207-21	SSUC207-21	1-5/16 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb

SSUC207-22	SSUC207-22	1-3/8 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb
SSUC207	SSUC207	35 mm	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb
SSUC207-23	SSUC207-23	1-7/16 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb
SSUC208-24	SSUC208-24	1-1/2 in	80.0 mm 3.150 in	49.2 mm 1.937 in	21.0 mm 0.827 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb
SSUC208-25	SSUC208-25	1-9/16 in	80.0 mm 3.150 in	49.2 mm 1.937 in	21.0 mm 0.827 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb
SSUC208	SSUC208	40 mm	80.0 mm 3.150 in	49.2 mm 1.937 in	21.0 mm 0.827 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb
SSUC209-26	SSUC209-26	1-5/8 in	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb
SSUC209-27	SSUC209-27	1-11/16 in	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb
SSUC209-28	SSUC209-28	1-3/4 in	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb
SSUC209	SSUC209	45 mm	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb
SSUC210-30	SSUC210-30	1-7/8 in	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb
SSUC210-31	SSUC210-31	1-15/16 in	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb
SSUC210	SSUC210	50 mm	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb
SSUC210-32	SSUC210-32	2 in	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb
SSUC211-32	SSUC211-32	2 in	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb
SSUC211-34	SSUC211-34	2-1/8 in	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb
SSUC211	SSUC211	55 mm	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb
SSUC211-35	SSUC211-35	2-3/16 in	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb
SSUC212-36	SSUC212-36	2-1/4 in	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb
SSUC212	SSUC212	60 mm	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb
SSUC212-38	SSUC212-38	2-3/8 in	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb
SSUC212-39	SSUC212-39	2-7/16 in	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb
SSUC213-40	SSUC213-40	2-1/2 in	120.0 mm 4.724 in	65.1 mm 2.563 in	28.0 mm 1.102 in	57.2 kN 126.1 lb	40.1 kN 88.4 lb
SSUC213	SSUC213	65 mm	120.0 mm 4.724 in	65.1 mm 2.563 in	28.0 mm 1.102 in	57.2 kN 126.1 lb	40.1 kN 88.4 lb
SSUC214-44	SSUC214-44	2-3/4 in	125.0 mm 4.921 in	74.6 mm 2.937 in	30.0 mm 1.181 in	62.2 kN 137.1 lb	44.1 kN 97.2 lb
SSUC214	SSUC214	70 mm	125.0 mm 4.921 in	74.6 mm 2.937 in	30.0 mm 1.181 in	62.2 kN 137.1 lb	44.1 kN 97.2 lb
SSUC215-47	SSUC215-47	2-15/16 in	130.0 mm 5.118 in	77.8 mm 3.063 in	32.0 mm 1.260 in	67.4 kN 148.6 lb	48.3 kN 106.5 lb
SSUC215	SSUC215	75 mm	130.0 mm 5.118 in	77.8 mm 3.063 in	32.0 mm 1.260 in	67.4 kN 148.6 lb	48.3 kN 106.5 lb
SSUC215-48	SSUC215-48	3 in	130.0 mm 5.118 in	77.8 mm 3.063 in	32.0 mm 1.260 in	67.4 kN 148.6 lb	48.3 kN 106.5 lb
SSUC216-50	SSUC216-50	3-1/8 in	140.0 mm 5.512 in	82.6 mm 3.252 in	33.0 mm 1.299 in	72.7 kN 160.3 lb	53.0 kN 116.8 lb
SSUC216	SSUC216	80 mm	140.0 mm 5.512 in	82.6 mm 3.252 in	33.0 mm 1.299 in	72.7 kN 160.3 lb	53.0 kN 116.8 lb
SSUC217-52	SSUC217-52	3-1/4 in	150.0 mm 5.906 in	85.7 mm 3.374 in	35.0 mm 1.378 in	84.0 kN 185.2 lb	61.9 kN 136.5 lb
SSUC217	SSUC217	85 mm	150.0 mm 5.906 in	85.7 mm 3.374 in	35.0 mm 1.378 in	84.0 kN 185.2 lb	61.9 kN 136.5 lb
SSUC218-56	SSUC218-56	3-1/2 in	160.0 mm 6.299 in	96.0 mm 3.780 in	38.0 mm 1.496 in	96.1 kN 211.9 lb	71.5 kN 157.6 lb
SSUC218	SSUC218	90 mm	160.0 mm 6.299 in	96.0 mm 3.780 in	38.0 mm 1.496 in	96.1 kN 211.9 lb	71.5 kN 157.6 lb